

SPWC Series

Common Mode Choke Wire Wound Type






FEATURES


- ◆The series are wire wound common mode chokes with maganetic shield.
- ◆Excellent solderability and resistance to soldering heat .
- ◆Good dimensions, high reliability and easy surface mount assembly.
- ◆Lower DC resistance, higher current tolerance and much stable performance,

APPLICATIONS

- ◆Notebooks
- **♦**PC's
- **◆USB**
- **♦**HUB







DIMENSIONS (mm)

| No. | Part No. | Size (mm) | | | | |
|-----|-----------|------------|------------|------------|-----|-----|
| NO. | Part NO. | Α | В | С | D | E |
| 1 | SPWC 1206 | 3.2 ± 0.10 | 1.6 ± 0.10 | 1.9 ± 0.10 | 0.6 | 0.6 |

SERIES LIST


| No. | Part No. | Impedance (Ω) at 100MHz | RDC (Ω) Max. | IDC (mA) Max. |
|-----|---------------|----------------------------------|-----------------|------------------|
| 1 | SPWC 1206-900 | 90 | 0.3 | 370 |
| 2 | SPWC 1206-161 | 160 | 0.4 | 340 |
| 3 | SPWC 1206-261 | 260 | 0.5 | 310 |
| 4 | SPWC 1206-601 | 600 | 0.8 | 260 |
| 5 | SPWC 1206-102 | 1000 | 1.0 | 230 |
| 6 | SPWC 1206-222 | 2200 | 1.2 | 200 |

RECOMMENDED PATTERN

| Type | Α | В | С | D | E |
|-----------|-----|-----|-----|-----|-----|
| SPWC 1206 | 3.8 | 1.6 | 0.4 | 1.1 | 1.6 |

PACKAGE

| Type | SPWC |
|-----------|-------|
| Q'TY/Reel | 2,000 |



info@schmid-m.com