



SDR-20-24 M

MODEL

OUTPUT	DC VOLTAGE	24V
	RATED CURRENT	1A
	RATED POWER	24W
	RIPPLE & NOISE (max.) Note.2	150mVp-p
	VOLTAGE ADJ. RANGE	21.6 ~ 26.4V
	VOLTAGE TOLERANCE Note.3	±1.0%
	LINE REGULATION	±1.0%
	LOAD REGULATION	±1.0%
	SETUP.RISE TIME	500ms, 30ms/230VAC 1000ms, 30ms/115VAC at full load
	HOLD UP TIME (Typ.)	50ms/230VAC 20ms/115VAC at full load
INPUT	VOLTAGE RANGE Note.5	85 ~ 264VAC 120~370VDC
	FREQUENCYRANGE	47~63HZ
	EFFICIENCY (Typ.)	84%
	AC CURRENT (Typ.)	0.55A/115VAC 0.35A/230VAC
	INRUSH CURRENT (max.)	COLD START 20A/115VAC 40A/230VAC
	SIZE	22.5*90*100mm (W*H*D) 0.18kg/pc
PROTECTION	OVERLOAD	105 ~ 160% rated output power Protection type : Constant current limiting, recovers automatically after fault condition is removed
	OVER VOLTAGE	27.6 ~ 32.4V Protection type : Shut down o/p voltage, re-power on to recover

